



Black Jade Series

MONO-FACIAL N-TYPE MODULE

490~500 W



Cutting Free Technology
Minimized micro-crack



Anti-PID (potential induced degradation)
Passed anti-PID test under 85% damp heat
85% relative humidity for 192 hours



Higher Power Output
Lower shading and resistive loss



Outstanding mechanical load resistance
2400 Pa wind load, 5400 Pa snow load



15 15-year product warranty
30 30-year linear power output



CEC Listed



IEC 61215, IEC 61730

ISO 9001: 2015 (Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO 45001: 2018 (Occupational health and safety)

UNI 9177 Ia CLASSE DI REAZIONE AL FUOCO:1

Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo, China

Tel: +86-574-28828939

Email: sales@ulsolar.com.cn

Fax: +86-574-28828997

Web: www.ulicasolar.com



TOPCon(N TYPE) 490~500Watt




ELECTRICAL SPECIFICATIONS

Module Type		UL-490M-120BHVN		UL-495M-120BHVN		UL-500M-120BHVN	
		STC* NOCT*	STC* NOCT*	STC* NOCT*	STC* NOCT*		
Maximum Power (Pmax)	W	490	371	495	375	500	379
Maximum Power Voltage (Vmp)	V	36.68	33.75	36.85	33.90	37.02	34.06
Maximum Power Current (Imp)	A	13.36	11.00	13.43	11.06	13.51	11.13
Open-circuit Voltage (Voc)	V	43.35	39.45	43.52	39.60	43.78	39.84
Short-circuit Current (Isc)	A	14.35	11.58	14.43	11.64	14.48	11.68
Module Efficiency STC	%	22.14		22.36		22.59	
Operating Temperature		-40°C~85°C					
Maximum system voltage		DC1500V(IEC)					
Maximum series fuse rating		25A					
Power tolerance		0~+5Watt					
Temperature coefficients of Pmax		-0.29%/°C					
Temperature coefficients of Voc		-0.25%/°C					
Temperature coefficients of Isc		0.046%/°C					
Nominal operating cell temperature (NOCT)		43±2°C					


*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G

*NOCT : Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s




SPECIFICATIONS

Cell Type	N type Mono-crystalline
No. of cells	120(6×10×2)
Dimensions	1952*1134*30mm
Weight	22.5kg
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Junction Box	IP68, 3diodes
Connector	MC4 Compatible
Cable Length (Including Connector)	4m Portrait:(+400/(-)200mm Landscape:(+1200/(-)1200mm
Packaging Configuration	Two Box=One Pallet 36pcs/Box, 72pcs/Pallet, 864pcs/40HQ Container



I-V CURVE[495W]

I-V characteristics at different irradiances



I-V characteristics at different temperature

